

# Crystal Clear Clarity In a Compact Package




Jandy Pro/Seri

# Jandy<sup>®</sup> Pro Series CS Series Single Element Cartridge Filters

The CS Filters utilize single element cartridges designed to provide the same great filtration as the CV and CL Models, but in a more compact body. The cartridges on the CS are easily removed, making it simple to clean and care for. Available in 100, 150, 200, and 250 square foot models.

- Compact body designed to easily fit into small areas
- Compatible with the Jandy Versa Plumb<sup>®</sup> System
- High-impact, corrosion and UV resistant, thermoplastic tank body
- Pressure gauge with clean/dirty indicator that makes it easy to assess filter condition
- Ergonomic, easy grip handles for ease of service
- Includes 2" x 2 1/2" universal unions
- Extra large 2" drain port for easy cleaning of debris

## DIMENSIONS



## SPECIFICATIONS

Model Number	CS100	CS150	CS200	CS250
Filter Area (ft2)	100	150	200	250
Normal Start Up PSI	6-15	6-15	6-15	6-15
Max Working PSI	50	50	50	50
Cartridges Required	1	1	1	1
Shipping Weight (lbs.)	28	28	28	28
Height - Dimension "A"	32 3/8"	32 3/8"	42 1/2"	42 1/2"

Residential Specifications							
Design Flow Rate (gpm/ft2)	1.00	0.85	0.625	0.50			
Maximum Flow (gpm)	100	125	125	125			
6 Hour Capacity (gallons)	36,000	45,000	45,000	45,000			
8 Hour Capacity (gallons)	48,000	60,000	60,000	60,000			

Commercial Specifications							
Design Flow Rate (gpm/ft2)	0.375	0.375	0.375	0.375			
Maximum Flow (gpm)	37	56	75	93			
6 Hour Capacity (gallons)	13,500	20,250	27,000	33,750			
8 Hour Capacity (gallons)	18,000	27,000	36,000	45,000			

### PERFORMANCE

### CS Filter Head Loss Curve

