

MORE POWER. MORE POSSIBILITIES.



Built Small. Built Strong. Built Jandy.®

With a 20% improvement in hydraulic performance¹, dual voltage capability, plus two auxiliary relays, the VS FloPro[™] delivers more possibilities than ever before.

• Powerful Performance

The improved VS FloPro 2.7HP now generates higher head pressure and flow rates to accommodate large pool and spa designs with features such as waterfalls, jets, in-floor cleaning and solar heating systems.

• Programmable Auxiliary Relays for Instant Automation Two programmable² auxiliary relays allow the pump to control other equipment, such as a salt chlorinator and booster pump, without a separate timeclock.





• 115v/230v Dual Voltage Capability

The ability to operate with either 115v or 230v power sources provides installation flexibility and eliminates expensive main power rewiring, making the VS FloPro 2.7HP the ideal aftermarket replacement pump.

• Lower Electricity Costs

Save over \$1,100³ per year in energy costs! The variable-speed motor allows for dramatic energy savings and quieter operation.

Choose Your Own Controller

Designed to work with the following Jandy control systems for complete programmability and customization:

- > SpeedSet Controller (included and preinstalled from factory on all DV2AS models)
- > iQPUMP01 with iAquaLink® App Control
- > Jandy AquaLink® Automation Sysytems
- > JEP-R Controller

Additional Features

- > Adjustable base for seamless direct replacement of a variety of other pumps in the aftermarket
- > Zero Clearance TEFC Motor for cool, quiet operation in tight spaces
- > 2" unions included or utilize 2" internal threads
- > Easy Controller Setup auto detects connection to an automation system or a traditional controller, eliminating the need to adjust settings manually
- RS485 Quick Connect Port for faster installation and maintenance
- Four-Speed Dry Contact Relay Control
- > Tool-free lid for easy debris removal
- > Ergonomic easy-transport handle

A Fluidra Brand | Jandy.com | 1.800.822.7933

MODELS

Model No.	Option Description
VSFHP270DV2AS	VS FloPro 2.7 HP, SpeedSet Controller Preinstalled
VSFHP270DV2A	VS FloPro 2.7 HP, Controller Sold Separately


SPECIFICATIONS

Model No.	ТНР	WEF ⁴	Voltage	Max Watts	Amps		Rec. Pipe Size ⁵	Carton Weight	
VSFHP270DV2A(S)	2.70	7.3	230 VAC	2,550W	10.5	2"	2" - 3"	53 lbs.	2/, 1/2"
VOI TII Z/UDVZA(O)	2.70	8.7	115 VAC	1.840W	16.0	2	2 - 3	JJ LDS.	24 1/2


ADJUSTABLE BASE CONFIGURATIONS⁶

Base	Fits	'A' Dimension	'B' Dimension
No Base	Hayward® Super Pump®, Pentair® SuperFlo®, Sta-Rite® SuperMax®	7-3/4"	12-3/4"
Small Base	Hayward Super II™, Jandy PlusHP and MaxHP Pumps	8-7/8"	13-7/8"
Small Base w/ Spacers	Pentair WhisperFlo® and IntelliFlo® VSF, Sta-Rite Dyna-Glas™	9-1/8"	14-1/8"
Small Base + Large Base	Sta-Rite Max-E-Pro®, Sta-Rite Dura-Glas®, Sta-Rite Dura-Glas II, Sta-Rite Max-E-Glas®	10-3/4"	15-3/4"

DIMENSIONS



PERFORMANCE



- ¹Hydraulic Horsepower of VSFHP270DV2A model compared to previous VSFHP270AUT / VSFHP270JEP models as measured on system curve C at 3450 RPM.

- as measured on system curve. at 3-a0 KFM.

 Auxiliary relays on all Jandy DYA and DYAS pump models are programmable when paired with a Jandy SpeedSet or iQPUMP01 variable-speed pump controller.

 Plased on a 28,000 gallon pold with two turnovers per day at an energy cost of \$0.195/kWh vs. comparable single speed pumps; when tested in accordance with the applicable requirements of 10 CFR 429.

 4WEF = weighted energy factor in kgal/kWh. WEF is a performance-based metric adopted by the Department of Energy to Characterize the energy performance of dedicated-purpose pool pumps.

 Department of Energy to CFR Parts 429 and 431.

 **Alwase follow local building and safety corder for nine sizing and quidelines.
- Always follow local building and safety codes for pipe sizing and guidelines

 Small base with spacers included with all FloPro pumps.

 Large base is optional part R0546400.





